



Main

| | |
|------------------------------------|--|
| Range | Prisma |
| Range compatibility | Prisma P |
| IP degree of protection | IP30 |
| Product or component type | Accessory |
| Accessory / separate part category | Spare part |
| Product compatibility | IP30 enclosure |
| Provided equipment | 2 roof and rear panel fixing systems 8 rear panel fixing systems 10 1/4 turn spacers 10 gaskets |

Complementary

| | |
|-------------------------------|------------|
| Mounting support | Rear panel |
| Enclosure/Cubicle description | Cubicle |
| Height | 25 mm |
| Width | 43 mm |
| Depth | 10 mm |
| Product weight | 0.22 kg |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1752 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Available |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|
