
# **Product datasheet**

Specifications





## TRANSPARENT FRONT PLATE WIDTH 600/650 6M

03343

() Discontinued on: 9 Aug 2023

### ① Discontinued

### Main

Range	Prisma
Range Of Product	Prisma G Prisma P
Product Or Component Type	Front plate
Accessory / Separate Part Category	Installation accessory
Range Compatibility	Prisma Prisma G enclosure Prisma Prisma P cubicle
Type Of Front Plate	Transparent
Installed Device	Power meters: kilowatt-hour meters - vertical installation connection TeSys: fixed GV3Pxx1 + LC1D40 to D65 - horizontal installation
Poles Description	3 x 2P: mounting plate support: kilowatt-hour meters vertical installation 2 x 4P: mounting plate support: kilowatt-hour meters vertical installation 7 x 3P: modular rail support: GV3Pxx1 + LC1D40 to D65 horizontal installation

### Complementary

Enclosure/Cubicle Description	Floor-standing enclosure - width 600mm Wall-mounted enclosure - width 600mm Cubicle - width 650mm depth 400mm Pack enclosure - width 555mm
Number Of Vertical Modules [50 Mm]	6
Standards	IEC 61439-1 IEC 61439-2
Product Certifications	ASEFA
Material	Glass
Surface Finish	Matt Smooth
Protective Treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Colour	White (RAL 9001)
Height	300 mm
Width	500 mm
Net Weight	1.38 kg
Quantity Per Set	Set of 1

#### Functional Unit

l Unit	600 mm Prisma G floor-standing enclosure power meters kilowatt-hour meters vertical 2P 3 6
	600 mm Prisma G wall-mounted enclosure power meters kilowatt-hour meters vertical 2P 3 6
	600 mm Prisma G floor-standing enclosure connection 2 6
	600 mm Prisma G wall-mounted enclosure connection 2 6
	650 mm 400 mm Prisma P cubicle connection 2 6
	600 mm Prisma G floor-standing enclosure TeSys GV3Pxx1 + LC1D40 to D65 fixed horizontal 3P 7 direct 7
	600 mm Prisma G wall-mounted enclosure TeSys GV3Pxx1 + LC1D40 to D65 fixed horizontal 3P 7 direct 7
	600 mm Prisma G floor-standing enclosure power meters kilowatt-hour meters vertical 4P 2 6
	600 mm Prisma G wall-mounted enclosure power meters kilowatt-hour meters vertical 4P 2 6
	650 mm 400 mm Prisma P cubicle power meters kilowatt-hour meters vertical 2P 3 6
	650 mm 400 mm Prisma P cubicle power meters kilowatt-hour meters vertical 4P 2 6

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.000 cm
Package 1 Width	30.000 cm
Package 1 Length	50.000 cm
Package 1 Weight	1.380 kg
Unit Type Of Package 2	CAR
Number Of Units In Package 2	8
Package 2 Height	17.000 cm
Package 2 Width	32.000 cm
Package 2 Length	53.000 cm
Package 2 Weight	13.800 kg
Unit Type Of Package 3	P12
Number Of Units In Package 3	48
Package 3 Height	49.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	82.800 kg

## Sustainability Screen

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

### Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes

### **Certifications & Standards**

Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
	Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile