
# **Product datasheet**

Specifications





## MOUNTING PLATE NS3200 INS-INV2500 FIXED VERTICAL IN WIDTH 650

03501

! Discontinued on: 9 Aug 2023

(!) Discontinued

#### Main

Range	Prisma
Range Of Product	Prisma P
Product Or Component Type	Mounting plate
Accessory / Separate Part Category	Installation accessory
Range Compatibility	Prisma Prisma P cubicle
Installation Description	Cubicle - width 650 mm depth 400 mm Cubicle - width 650 mm depth 600 mm
Installed Device	ComPact: fixed INS20002500 - control: direct front rotary handle - vertical installation ComPact: fixed INS630b1600 - control: direct front rotary handle - vertical
	installation ComPact: fixed INV20002500 - control: direct front rotary handle - vertical installation ComPact: fixed INV630b1600 - control: direct front rotary handle - vertical
	installation ComPact: fixed NS1600b - control: toggle - vertical installation ComPact: fixed NS20003200 - control: toggle - vertical installation
Poles Description	1 x 3P: fixed INS20002500 vertical installation 1 x 4P: fixed INS20002500 vertical installation 1 x 3P: fixed INS630b1600 vertical installation 1 x 4P: fixed INS630b1600 vertical installation 1 x 3P: fixed INV20002500 vertical installation 1 x 4P: fixed INV20002500 vertical installation 1 x 3P: fixed INV630b1600 vertical installation 1 x 3P: fixed INV630b1600 vertical installation 1 x 3P: fixed NS1600b vertical installation 1 x 3P: fixed NS1600b vertical installation 1 x 3P: fixed NS1600b vertical installation 1 x 3P: fixed NS20003200 vertical installation
Number Of Vertical Modules [50 Mm]	1 x 4P: fixed NS20003200 vertical installation  16 module(s): INS20002500, front connection on adaptor in 650 mm Widecubicle 16 module(s): INS20002500, rear connection on adaptor in 650 mm Widecubicle 14 module(s): INS630b1600, front connection on adaptor in 650 mm Widecubicle 16 module(s): INV20002500, front connection on adaptor in 650 mm Widecubicle 16 module(s): INV20002500, rear connection on adaptor in 650 mm Widecubicle 14 module(s): INV630b1600, front connection on adaptor in 650 mm Widecubicle 14 module(s): NS1600b, front connection on adaptor in 650 mm Widecubicle 16 module(s): NS20003200, front connection on adaptor in 650 mm Widecubicle
 Standards	IEC 61439-2
Product Certifications	ASEFA

### Complementary

Protective Treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Surface Finish	Matt Smooth

26 Apr 2024 Life Is On Schneider

Colour	White (RAL 9001)	
Width	650 mm	
Height	200 mm	
Net Weight	2.9 kg	
Functional Unit	650 mm 400 mm Prisma P cubicle ComPact INS20002500 fixed direct front rotary handle vertical 3P 1 front connection on adaptor 16 262.5 mm 650 mm 400 mm Prisma P cubicle ComPact INS20002500 fixed direct front rotary handle vertical 4P 1 front connection on adaptor 16 262.5 mm 650 mm 600 mm Prisma P cubicle ComPact INS20002500 fixed direct front rotary handle vertical 3P 1 rear connection on adaptor 16 262.5 mm 650 mm 600 mm Prisma P cubicle ComPact INS20002500 fixed direct front rotary handle vertical 4P 1 rear connection on adaptor 16 262.5 mm 650 mm 400 mm Prisma P cubicle ComPact INS630b1600 fixed direct front rotary handle vertical 3P 1 front connection on adaptor 14 262.5 mm 650 mm 400 mm Prisma P cubicle ComPact INS630b1600 fixed direct front rotary handle vertical 4P 1 front connection on adaptor 14 262.5 mm 650 mm 400 mm Prisma P cubicle ComPact INV20002500 fixed direct front rotary handle vertical 3P 1 front connection on adaptor 16 262.5 mm 650 mm 400 mm Prisma P cubicle ComPact INV20002500 fixed direct front rotary handle vertical 3P 1 front connection on adaptor 16 262.5 mm 650 mm 600 mm Prisma P cubicle ComPact INV20002500 fixed direct front rotary handle vertical 3P 1 rear connection on adaptor 16 262.5 mm 650 mm 600 mm Prisma P cubicle ComPact INV20002500 fixed direct front rotary handle vertical 3P 1 rear connection on adaptor 16 262.5 mm 650 mm 600 mm Prisma P cubicle ComPact INV20002500 fixed direct front rotary handle vertical 3P 1 front connection on adaptor 14 262.5 mm 650 mm 400 mm Prisma P cubicle ComPact INV630b1600 fixed direct front rotary handle vertical 4P 1 rear connection on adaptor 14 262.5 mm 650 mm 400 mm Prisma P cubicle ComPact INV630b1600 fixed direct front rotary handle vertical 4P 1 front connection on adaptor 14 262.5 mm 650 mm 400 mm Prisma P cubicle ComPact INV630b1600 fixed toggle vertical 3P 1 front connection on adaptor 14 212.5 mm 650 mm 600 mm Prisma P cubicle ComPact NS1600b fixed toggle vertical 4P 1 front connection on ada	

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.5 cm
Package 1 Width	20.0 cm
Package 1 Length	59.0 cm
Package 1 Weight	2.9 kg
Unit Type Of Package 2	S04
Number Of Units In Package 2	6
Package 2 Height	30.0 cm
Package 2 Width	40.0 cm
Package 2 Length	60.0 cm
Package 2 Weight	17.4 kg



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance

	Mercury Free	
<b>⊘</b>	Rohs Exemption Information	Yes
<b>⊘</b>	Halogen Free Plastic Parts Product	

#### **Certifications & Standards**

Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information