
# **Product datasheet**

Specifications

Sreen Premium<sup>™</sup>



## LINERGY FC DISTRIBUTION BLOCK FOR COMPACT NSX250 4P FIXED/PLUG-IN+CONNECTION

04406

() Discontinued on: 10 Dec 2021

Main

Range	Linergy	
Range Of Product	Linergy	
Product Or Component Type	Device feeder	
Product Name	Linergy FC	
Accessory / Separate Part Category	Connection accessory	
Range Compatibility	Prisma Prisma P cubicle	
Provided Equipment	Prefabricated flexible connection to Linergy busbars	

#### Complementary

Installation Description	Cubicle - width 650 mm
Number Of Devices	3 (4P)
Poles Description	4P

Installed Device	ComPact: fixed NSX100160 without earth leakage protection - control: direct front rotary handle - vertical installation
	ComPact: fixed NSX250 without earth leakage protection - control: direct front rotary handle - vertical installation
	ComPact: fixed NSX100160 without earth leakage protection - control: motor mechanism - vertical installation
	ComPact: fixed NSX250 without earth leakage protection - control: motor mechanism - vertical installation
	ComPact: plug-in NSX100160 without earth leakage protection - control: direct front rotary handle - vertical installation
	ComPact: plug-in NSX250 without earth leakage protection - control: direct front rotary handle - vertical installation
	ComPact: plug-in NSX100160 without earth leakage protection - control: motor
	mechanism - vertical installation ComPact: plug-in NSX250 without earth leakage protection - control: motor
	mechanism - vertical installation ComPact: plug-in NSX100160 without earth leakage protection - control: toggle -
	vertical installation ComPact: plug-in NSX250 without earth leakage protection - control: toggle - vertical
	installation
	ComPact: fixed NSX100160 with earth leakage protection - control: direct front rotary handle - vertical installation
	ComPact: fixed NSX250 with earth leakage protection - control: direct front rotary handle - vertical installation
	ComPact: fixed NSX100160 with earth leakage protection - control: motor mechanism - vertical installation
	ComPact: fixed NSX250 with earth leakage protection - control: motor mechanism -
	vertical installation ComPact: plug-in NSX100160 with earth leakage protection - control: direct front
	rotary handle - vertical installation ComPact: plug-in NSX250 with earth leakage protection - control: direct front rotary
	handle - vertical installation ComPact: plug-in NSX100160 with earth leakage protection - control: motor
	mechanism - vertical installation ComPact: plug-in NSX250 with earth leakage protection - control: motor mechanism -
	vertical installation
	ComPact: plug-in NSX100160 with earth leakage protection - control: toggle - vertical installation
	ComPact: plug-in NSX250 with earth leakage protection - control: toggle - vertical installation
Mounting Support	Mounting plate
Installation Direction	Horizontal
[Ui] Rated Insulation Voltage	750 V AC
[Uimp] Rated Impulse Withstand Voltage	8 kV
[le] Rated Operational Current	675 A at 40 °C
[Ue] Rated Operational Voltage	690 V
[lpk] Rated Peak Withstand Current	50 kA
I <sup>2</sup> T On Activation	25000000 A².s
Permissible Current	675 A at 40 °C
	615 A at 60 °C 570 A at 70 °C
Connections - Terminals	Outgoer: plug in (phase / neutral) , 3 outgoers Supply: flexible bars (phase / neutral) , 32 x 8 mm
Standards	IEC 61439-2 IEC 61439-1
Product Certifications	KEMA ASEFA
Quantity Per Set	Set of 1
Length	440 mm
Height	132 mm
Depth	235 mm
Net Weight	8 kg

Colour	Black
Packing Units	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	15 cm
Package 1 Width	24 cm
Package 1 Length	45.5 cm
Package 1 Weight	8.66 kg

### Sustainability Screen

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free	
Mercury Free	
Rohs Exemption Information	Yes

#### **Certifications & Standards**

Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information