



Main

| | |
|--------------------------------|------------------|
| Range of product | Canalis |
| Product name | KS |
| Product or component type | Adapter |
| Product compatibility | KS |
| [Ie] rated operational current | 400 A |
| Colour | White (RAL 9001) |

Complementary

| | |
|------------------------------------|------------------|
| Accessory / separate part category | Adaptation |
| Device application | Adapt old offer |
| Mounting location | Between trunking |
| Mounting mode | By screws |
| Mounting support | Busbar |
| Busbar trunking polarity | 3L + N + PE |
| Width | 324 mm |
| Depth | 95 mm |
| Height | 188.5 mm |
| Body material | Plastic |
| Net weight | 2.9 kg |

Environment

| | |
|-------------------------|------------------------------|
| IP degree of protection | IP55 conforming to IEC 60529 |
| Standards | IEC 61439-6 IEC 60439-2 |

Offer Sustainability

| | |
|--------------------------|-----------------------------------|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |

| | |
|----------------------------|---|
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations End of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

