



Main

Range of product	Canalis
Product name	KS
Product or component type	Busbar trunking
Busbar description	Transport length
BAR MATERIAL	Aluminium
Device application	Medium power distribution
[Ie] rated operational current	500 A at 35 °C
Number of tap-off outlets	0

Complementary

[Ue] rated operational voltage	230...690 V
Network frequency	50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ui] rated insulation voltage	690 V
[Icw] rated short-time withstand current	26.2 kA
[Ipk] rated peak withstand current	55 kA
Electrical connection	Lubricated sliding contact
Radiated magnetic field	0.66 µT
Thermal stress limit	733 kA ² .s
THDI	0...15 % 500 A 15...33 % 400 A 33...100 % 315 A
Maximum voltage drop	<0.013 V with power factor = 1 at 50 Hz with 1A for 100 m long <0.014 V with power factor = 0.9 at 50 Hz with 1A for 100 m long <0.014 V with power factor = 0.8 at 50 Hz with 1A for 100 m long <0.013 V with power factor = 0.7 at 50 Hz with 1A for 100 m long
Mounting mode	By screws
Mounting position	Horizontal
Neutral position	Up
Busbar trunking polarity	3L + N + PE

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Dimension type	Fix
Width	146 mm
Depth	113 mm
Length	5 m
Net weight	51.5 kg

Environment

Standards	IEC 60439-2 IEC 61439-6
-----------	----------------------------

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------

