# **Product datasheet**

Specifications





End feed unit, Canalis KSA630, aluminium, 500/630A, left mounting, for line protection, polarity 3L+N+PE, white RAL9001

KSA630ABGD4

### Main

Range Of Product	Canalis
Product Name	KS
Device Short Name	KSA
Product Compatibility	Canalis KSA busbar trunking 5001000 A
Offer Type	Advanced
Product Or Component Type	Feed unit
Conductors Material	Aluminium
[Ie] Rated Operational Current	630 A
[Ue] Rated Operational Voltage	230690 V
Number Of Circuits	1
Busbar Trunking Polarity	3L + N + PE
Protection Type	Circuit breaker protection
Control Type	Rotary handle
Colour	White (RAL 9001)

# Complementary

Mounting Location	Left	
Mounting Support	Busbar	
Body Material	Metal	
Connections - Terminals	Cable with lug Bars	
Width	1229 mm	
Depth	390 mm	
Height	457 mm	
Net Weight	39.2 kg	
Standards	IEC 61439-1 IEC 61439-6	

### Environment

Ip Degree Of Protection	IP55 conforming to IEC 60529
Ik Degree Of Protection	IK08 conforming to IEC 62262

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	39.9 cm
Package 1 Width	50 cm
Package 1 Length	123 cm
Package 1 Weight	44.86 kg

### **Contractual warranty**

Warranty

18 months

# Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

# Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes
Halogen Free Product

### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations

## **Product datasheet**

**Dimensions Drawings** 

#### Dimensions

