



### Main

Range of product	Canalis
Product name	KS
Product or component type	Busbar trunking
Busbar description	Riser foot
BAR MATERIAL	Aluminium
Device application	Rise medium power distribution
[Ie] rated operational current	630 A at 35 °C
Number of tap-off outlets	1

### Complementary

[Ue] rated operational voltage	230...690 V
Network frequency	50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ui] rated insulation voltage	690 V
[Icw] rated short-time withstand current	32.1 kA
[Ipk] rated peak withstand current	67.5 kA
Electrical connection	Lubricated sliding contact
Radiated magnetic field	0.89 µT
Thermal stress limit	1225 kA <sup>2</sup> .s
THDI	0...15 % 630 A 15...33 % 500 A 33...100 % 400 A
Maximum voltage drop	<0.011 V with power factor = 1 at 50 Hz with 1A for 100 m long <0.013 V with power factor = 0.9 at 50 Hz with 1A for 100 m long <0.013 V with power factor = 0.8 at 50 Hz with 1A for 100 m long <0.012 V with power factor = 0.7 at 50 Hz with 1A for 100 m long
Mounting mode	By screws
Mounting support	Foot riser
Mounting position	Vertical - neutral on right
Neutral position	Right

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Busbar trunking polarity	3L + N + PE
Dimension type	Fix
Width	146 mm
Depth	113 mm
Height	800 mm
Length	0.8 m
Net weight	12.1 kg

## Environment

Standards	IEC 61439-6 IEC 60439-2
-----------	----------------------------

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">Download RoHS China Declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations <a href="#">End of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------

