# **Product datasheet**

Specifications





# Contactor, TeSys Deca, 3P(3NO), AC-3/AC-3e, <=440V, 18A, 415V AC 50/60Hz coil, screw clamp terminals

LC1D18N7

### Main

| Range Of Product               | TeSys Deca  |  |
|--------------------------------|---|--|
| Product Or Component Type      | Contactor   |  |
| Device Short Name              | LC1D  |  |
| Contactor Application          | Resistive load<br>Motor control   |  |
| Utilisation Category           | AC-1<br>AC-4<br>AC-3<br>AC-3e   |  |
| Poles Description              | 3P  |  |
| [Ue] Rated Operational Voltage | Power circuit: <= 690 V AC 25400 Hz<br>Power circuit: <= 300 V DC   |  |
| [le] Rated Operational Current | 18 A (at <60 °C) at <= 440 V AC AC-3 for power circuit<br>32 A (at <60 °C) at <= 440 V AC AC-1 for power circuit<br>18 A (at <60 °C) at <= 440 V AC AC-3e for power circuit |  |
| [Uc] Control Circuit Voltage   | 415 V AC 50/60 Hz   |  |

### Complementary

| Motor Power Kw                                 | 4 kW at 220230 V AC 50/60 Hz (AC-3)<br>7.5 kW at 380400 V AC 50/60 Hz (AC-3)<br>9 kW at 415440 V AC 50/60 Hz (AC-3)<br>10 kW at 500 V AC 50/60 Hz (AC-3)<br>10 kW at 660690 V AC 50/60 Hz (AC-3)<br>4 kW at 400 V AC 50/60 Hz (AC-4)<br>4 kW at 220230 V AC 50/60 Hz (AC-3e)<br>7.5 kW at 380400 V AC 50/60 Hz (AC-3e)<br>9 kW at 415440 V AC 50/60 Hz (AC-3e)<br>10 kW at 500 V AC 50/60 Hz (AC-3e)<br>10 kW at 660690 V AC 50/60 Hz (AC-3e) |  |
|--|---|--|
| Motor Power Hp                                 | 1 hp at 115 V AC 50/60 Hz for 1 phase motors<br>3 hp at 230/240 V AC 50/60 Hz for 1 phase motors<br>5 hp at 200/208 V AC 50/60 Hz for 3 phases motors<br>5 hp at 230/240 V AC 50/60 Hz for 3 phases motors<br>10 hp at 460/480 V AC 50/60 Hz for 3 phases motors<br>15 hp at 575/600 V AC 50/60 Hz for 3 phases motors  |  |
| Compatibility Code                             | LC1D  |  |
| Pole Contact Composition                       | 3 NO  |  |
| Protective Cover                               | With  |  |
| [Ith] Conventional Free Air<br>Thermal Current | 10 A (at 60 °C) for signalling circuit<br>32 A (at 60 °C) for power circuit   |  |
| Irms Rated Making Capacity                     | 140 A AC for signalling circuit conforming to IEC 60947-5-1<br>250 A DC for signalling circuit conforming to IEC 60947-5-1<br>300 A at 440 V for power circuit conforming to IEC 60947  |  |
| Rated Breaking Capacity                        | 300 A at 440 V for power circuit conforming to IEC 60947  |  |

| [Icw] Rated Short-Time Withstand          | 145 A 40 °C - 10 s for power circuit   |
|---|--|
| Current                                   | 240 A 40 °C - 1 s for power circuit  |
|   | 40 A 40 °C - 10 min for power circuit  |
|   | 84 A 40 °C - 1 min for power circuit   |
|   | 100 A - 1 s for signalling circuit   |
|   | 120 A - 500 ms for signalling circuit  |
|   | 140 A - 100 ms for signalling circuit  |
| Associated Fuse Rating                    | 10 A gG for signalling circuit conforming to IEC 60947-5-1   |
|   | 50 A gG at <= 690 V coordination type 1 for power circuit  |
|   | 35 A gG at <= 690 V coordination type 2 for power circuit  |
| Average Impedance                         | 2.5 mOhm - Ith 32 A 50 Hz for power circuit  |
| Power Dissipation Per Pole                | 2.5 W AC-1   |
|   | 0.8 W AC-3   |
|   | 0.8 W AC-3e  |
| [Ui] Rated Insulation Voltage             | Power circuit: 690 V conforming to IEC 60947-4-1   |
|   | Power circuit: 600 V CSA certified   |
|   | Power circuit: 600 V UL certified  |
|   | Signalling circuit: 690 V conforming to IEC 60947-1  |
|   | Signalling circuit: 600 V CSA certified  |
|   | Signalling circuit: 600 V UL certified   |
| Overvoltage Category                      | Ш  |
| Pollution Degree                          | 3  |
| [Uimp] Rated Impulse Withstand<br>Voltage | 6 kV conforming to IEC 60947   |
| Safety Reliability Level                  | B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1<br>B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO |
|   | 13849-1  |
| Mechanical Durability                     | 15 Mcycles   |
| Electrical Durability                     | 1.65 Mcycles 18 A AC-3 at Ue <= 440 V  |
|   | 1 Mcycles 32 A AC-1 at Ue <= 440 V   |
|   | 1.65 Mcycles 18 A AC-3e at Ue <= 440 V   |
| Control Circuit Type                      | AC at 50/60 Hz   |
| Coil Technology                           | Without built-in suppressor module   |
| Control Circuit Voltage Limits            | 0.30.6 Uc (-4070 °C):drop-out AC 50/60 Hz  |
|   | 0.81.1 Uc (-4060 °C):operational AC 50 Hz  |
|   | 0.851.1 Uc (-4060 °C):operational AC 60 Hz   |
|   | 11.1 Uc (6070 °C):operational AC 50/60 Hz  |
| Inrush Power In Va                        | 70 VA 60 Hz cos phi 0.75 (at 20 °C)  |
|   | 70 VA 50 Hz cos phi 0.75 (at 20 °C)  |
| Hold In Power Consumption In Ma           |  |
| Hold-In Power Consumption In Va           | 7.5 VA 60 Hz cos phi 0.3 (at 20 °C)<br>7 VA 50 Hz cos phi 0.3 (at 20 °C)   |
| Heat Dissipation                          | 23 W at 50/60 Hz   |
| Operating Time                            | 1222 ms closing  |
|   | 419 ms opening   |
| Maximum Operating Rate                    | 3600 cyc/h 60 °C   |
|   |  |

| <b>Connections - Terminals</b> | Control circuit: screw clamp terminals 1 14 mm <sup>2</sup> - cable stiffness: flexible without   |
|--------------------------------|---|
|                                | cable end   |
|                                | Control circuit: screw clamp terminals 2 14 mm <sup>2</sup> - cable stiffness: flexible without<br>cable end  |
|                                | Control circuit: screw clamp terminals 1 14 mm <sup>2</sup> - cable stiffness: flexible with cable  |
|                                | end   |
|                                | Control circuit: screw clamp terminals 2 12.5 mm <sup>2</sup> - cable stiffness: flexible with<br>cable end   |
|                                | Control circuit: screw clamp terminals 1 14 mm <sup>2</sup> - cable stiffness: solid without<br>cable end   |
|                                | Control circuit: screw clamp terminals 2 14 mm <sup>2</sup> - cable stiffness: solid without<br>cable end   |
|                                | Power circuit: screw clamp terminals 1 1.56 mm <sup>2</sup> - cable stiffness: flexible without cable end   |
|                                | Power circuit: screw clamp terminals 2 1.56 mm <sup>2</sup> - cable stiffness: flexible without cable end   |
|                                | Power circuit: screw clamp terminals 1 16 mm <sup>2</sup> - cable stiffness: flexible with cable end  |
|                                | Power circuit: screw clamp terminals 2 14 mm <sup>2</sup> - cable stiffness: flexible with cable end  |
|                                | Power circuit: screw clamp terminals 1 1.56 mm <sup>2</sup> - cable stiffness: solid without<br>cable end   |
|                                | Power circuit: screw clamp terminals 2 1.56 mm <sup>2</sup> - cable stiffness: solid without cable end  |
| Tightening Torque              | Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm<br>Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2<br>Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm       |
|                                | Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2<br>Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver pozidriv No 2<br>Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver pozidriv No 2 |
| Auxiliary Contact Composition  | 1 NO + 1 NC   |
| Auxiliary Contacts Type        | type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1<br>type mirror contact 1 NC conforming to IEC 60947-4-1  |
| Signalling Circuit Frequency   | 25400 Hz  |
| Minimum Switching Voltage      | 17 V for signalling circuit   |
| Minimum Switching Current      | 5 mA for signalling circuit   |
| Insulation Resistance          | > 10 MOhm for signalling circuit  |
| Non-Overlap Time               | 1.5 ms on de-energisation between NC and NO contact<br>1.5 ms on energisation between NC and NO contact   |
| Mounting Support               | Rail  |
|                                |   |

## Environment

| Standards               | CSA C22.2 No 14  |
|-------------------------|--|
|                         | EN 60947-4-1   |
|                         | EN 60947-5-1   |
|                         | IEC 60947-4-1  |
|                         | IEC 60947-5-1  |
|                         | UL 508   |
|                         | IEC 60335-1  |
| Product Certifications  | GOST   |
|                         | CSA  |
|                         | RINA   |
|                         | DNV  |
|                         | CCC  |
|                         | LROS (Lloyds register of shipping)                                 |
|                         | UL   |
|                         | BV   |
|                         | GL   |
|                         | UKCA   |
| Ip Degree Of Protection | IP20 front face conforming to IEC 60529                            |
| Protective Treatment    | TH conforming to IEC 60068-2-30                                    |
| Climatic Withstand      | conforming to IACS E10 exposure to damp heat                       |
|                         | conforming to IEC 60947-1 Annex Q category D exposure to damp heat |

| Permissible Ambient Air       | -4060 °C                                    |
|-------------------------------|---|
| Temperature Around The Device | 6070 °C with derating                       |
|                               | ······································      |
| Operating Altitude            | 03000 m                                     |
|                               |   |
| Fire Resistance               | 850 °C conforming to IEC 60695-2-1          |
| <u> </u>                      |   |
| Flame Retardance              | V1 conforming to UL 94                      |
| Mechanical Robustness         | Vibrations contactor open (2 Gn, 5300 Hz)   |
|                               |   |
|                               | Vibrations contactor closed (4 Gn, 5300 Hz) |
|                               | Shocks contactor open (10 Gn for 11 ms)     |
|                               | Shocks contactor closed (15 Gn for 11 ms)   |
| Height                        | 77 mm                                       |
|                               |   |
| Width                         | 45 mm                                       |
|                               |   |
| Depth                         | 86 mm                                       |
|                               |   |
| Net Weight                    | 0.33 kg                                     |
|                               |   |

# **Packing Units**

| Unit Type Of Package 1       | PCE       |
|------------------------------|-----------|
| Number Of Units In Package 1 | 1         |
| Package 1 Height             | 5.000 cm  |
| Package 1 Width              | 9.200 cm  |
| Package 1 Length             | 11.200 cm |
| Package 1 Weight             | 359.000 g |
| Unit Type Of Package 2       | S02       |
| Number Of Units In Package 2 | 20        |
| Package 2 Height             | 15.000 cm |
| Package 2 Width              | 30.000 cm |
| Package 2 Length             | 40.000 cm |
| Package 2 Weight             | 7.524 kg  |

# **Contractual warranty**

Warranty

18 months

# Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

## Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes
Pvc Free

### **Certifications & Standards**

| Reach Regulation         | REACh Declaration   |
|--------------------------|---|
| Eu Rohs Directive        | Compliant<br>EU RoHS Declaration  |
| China Rohs Regulation    | China RoHS declaration<br>Pro-active China RoHS declaration (out of China RoHS legal scope)                                 |
| Environmental Disclosure | Product Environmental Profile   |
| Weee                     | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile      | End of Life Information   |